

SAFETY DATA SHEET



Revision Date 26-Jul-2017

SDS Number 888100004452

Revision Number 2.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product Name Jet Fuel

Synonyms Jet Fuel - A, A-I, A-50, Aviation Turbine Fuel, Jet A-I, Jet A, Avjet For Blending, Jet Q Turbine Fuel, Aviation Fuel, Turbine Fuel, JP-8, Av-Jet, Sweet Distillate, APPC463, RS203

Recommended Use Fuel
Uses advised against All others

Manufacturer
Tesoro Refining & Marketing Co.
19100 Ridgewood Parkway
San Antonio, TX 78259

Emergency Telephone Chemtrec: 1-800-424-9300
Tesoro Call Center: 1-877-783-7676

E-mail address ProductStewardship@TSOCORP.com

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 3
Acute dermal toxicity	Category 4
Acute Inhalation Toxicity - Dusts and Mists	Category 4
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Chronic Aquatic Toxicity	Category 2
Aspiration toxicity	Category 1

Label elements

Danger

Flammable liquid and vapor
Harmful in contact with skin
Harmful if inhaled
May cause cancer
May cause damage to organs through prolonged or repeated exposure
Toxic to aquatic life with long lasting effects
May be fatal if swallowed and enters airways



Appearance Liquid

Physical State @20°C Liquid

Odor Characteristic petroleum or kerosene-like

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/or bond container and receiving equipment
Use explosion-proof electrical/ ventilating / lighting / equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Call a POISON CENTER or doctor if you feel unwell
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
Wash contaminated clothing before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting
In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful if swallowed. Causes mild skin irritation. Toxic to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Percent
Kerosene (petroleum)	8008-20-6	0-100
Naphthalene	91-20-3	0-3
Ethylbenzene	100-41-4	0-1
1,2,4-Trimethylbenzene	95-63-6	0-1

4. FIRST AID MEASURES

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Remove from exposure, lie down. In case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt, seek medical advice. Never give anything by mouth to an unconscious person. Take off all contaminated clothing immediately and thoroughly wash material from skin. Immediate medical attention is required.
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid breathing vapors or mists.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Small Fire	Any extinguisher suitable for Class B fires, dry chemical, CO2, foam (AFFF/ATC), or water spray can be used.
Large Fire	Water spray, fog or alcohol-resistant foam. CAUTION: Use of water spray when fighting fire may be inefficient. Cool containers with flooding quantities of water until well after fire is out.
Unsuitable extinguishing media	CAUTION: Use of water spray when fighting fire may be inefficient.
Specific hazards arising from the chemical	Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.). Vapors may form explosive mixture with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. May accumulate electrostatic charge and ignite or explode.
Hazardous combustion products	Smoke, CO, and other products of incomplete combustion.
Explosion data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	Yes.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible

withdraw from area and let fire burn.

Further information

ALWAYS stay away from tanks engulfed in fire. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Do not direct water at source of leak or safety devices; icing may occur. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

NFPA

Health hazards 1

Flammability 2

Stability 0

Physical and chemical properties -

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapors or mists.

Other Information

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Hydrocarbon liquids including this product can act as a non-conductive flammable liquid (or static accumulator), and may form ignitable vapor-air mixtures in storage tanks or other containers. Precautions to prevent static initiated fire or explosion during transfer, storage or handling, include but are not limited to these examples: (1) Ground and bond containers during product transfers. Grounding and bonding may not be adequate protection to prevent ignition or explosion of hydrocarbon liquid and vapors that are static accumulators.

(2) Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel or diesel) is loaded into tanks previously containing low flash point products (such as gasoline or naphtha). (3) Storage tank level floats must be effectively bonded. For more information on precautions to prevent static-initiated fire or explosion, see NFPA 77 Recommended Practice on Static Electricity and API Recommended Practice 2003 Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

Keep away from flame, sparks, excessive temperatures and open flame. Use approved containers. Keep containers closed and clearly labeled. Empty or partially full product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose containers to sources of ignition. Store in a well-ventilated area. The storage area should comply with NFPA 30 "Flammable and Combustible Liquid Code". The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 "Cleaning Mobile Tanks In Flammable and Combustible Liquid Service" and API RP 2015 "Cleaning Petroleum Storage Tanks". Keep away from food, drink and animal feed. Incompatible with oxidizing agents. Incompatible with acids. Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	ACGIH TLV	OSHA PEL
Kerosene (petroleum) 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures S****	-
Naphthalene 91-20-3	TWA: 10 ppm S****	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³ ***
Ethylbenzene 100-41-4	TWA: 20 ppm***	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³ ***

S* - Potential exposure by cutaneous route

NOTE: Limits shown for guidance only. For additional information, OSHA's 1989 air contaminants standard exposure limits provided even though the limits were vacated in 1992. State, local or other agencies or advisory groups may have established more stringent limits. Follow applicable regulations.

Appropriate engineering controls

Engineering controls

- Showers
- Eyewash stations
- Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Hand Protection	Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use a NIOSH approved respirator when there is a potential for airborne concentrations to exceed occupational exposure limits. Refer to OSHA 29 CFR 1910.134, ANSI Z88.2, NIOSH Respirator Decision Logic, and the respirator manufacturer for additional guidance on respiratory protection selection. A Self-Contained Breathing Apparatus (SCBA) should be used for fire fighting. Use a NIOSH approved positive-pressure supplied air respirator if there is a potential for uncontrolled release, exposure levels are unknown, in oxygen deficient (less than 19.5% oxygen), or any other circumstance where an air-purifying respirator may not provide adequate protection.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State @20°C	Liquid
Appearance	Liquid
Odor	Characteristic petroleum or kerosene-like
Color	Clear to straw
Odor threshold	0.1 - 1 ppm

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	
Melting point / freezing point	-26 °C / -15 °F	
Boiling range	154 - 154 to 372 °C	
Flash point	38 °C / 100 °F	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable	
Flammability Limit in Air %		
Upper flammability limit:	5.0	
Lower flammability limit:	0.7	
Vapor pressure	< 0.267	
Vapor density	> 4.5	
Relative density	0.8	
Water solubility	0.0005 g/100 mL	
Solubility in other solvents	No data available	
Partition coefficient	3.3 to 6	
Autoignition temperature	238 °C / 460 °F	
Decomposition temperature	No data available	
Kinematic viscosity	1.6 mm ² /s	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidizing properties	No data available	
Minimum Ignition Energy (mJ)	No data available	
K_{st} (bar.m/s)	No data available	
Softening point	No data available	
VOC Content (%)	No data available	
Density	No data available	
Bulk density	Not applicable	
Conductivity	Diesel Fuel Oils at terminal load rack: At least 25 pS/m. Ultra Low Sulfur Diesel (ULSD)	

without conductivity additive: 0 pS/m to 5 pS/m. ULSD at terminal load rack with conductivity additive: At least 50 pS/m. JP-8 at terminal load rack: 150 pS/m to 600 pS/m.

10. STABILITY AND REACTIVITY

Reactivity	This product is non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	Oxidizing or reducing agents. Acids. Alkali.
Hazardous decomposition products	None under normal use conditions.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
Eye contact	May cause irritation.
Skin contact	Repeated exposure may cause skin dryness or cracking. May be absorbed through the skin in harmful amounts. Harmful in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Information on toxicological effects

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	3,764.00 mg/kg
ATEmix (dermal)	1,987.00 mg/kg
ATEmix (inhalation-dust/mist)	2.70 mg/l

Chemical Name	Oral LD50	LD50/dermal/rat - NO UNITS (Wizards mg/kg)	Inhalation LC50
Kerosene (petroleum) 8008-20-6	> 5000 mg/kg (Rat)***	> 2000 mg/kg (Rabbit)***	> 5.28 mg/L (Rat) 4 h***
Naphthalene 91-20-3	= 1110 mg/kg (Rat) = 490 mg/kg (Rat)***	= 1120 mg/kg (Rabbit) > 20 g/kg (Rabbit)***	> 340 mg/m ³ (Rat) 1 h***
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)***	= 15400 mg/kg (Rabbit)***	= 17.4 mg/L (Rat) 4 h***
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)***	> 3160 mg/kg (Rabbit)***	= 18 g/m ³ (Rat) 4 h***

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name

Naphthalene

Acute (short term) exposure to large amounts of naphthalene may damage or destroy red blood cells, a condition termed hemolytic anemia. Symptoms of hemolytic anemia include fatigue, lack of appetite, restlessness, and pale skin. Acute inhalation or oral exposure to large amounts of naphthalene may also cause nausea, vomiting, diarrhea, blood in the urine, and a yellow color to the skin. Ingestion may result in death. Chronic (long term) exposure in rats and mice can lead to irritation and inflammation of their nose and lungs; nasal hyperplasia and metaplasia in respiratory and olfactory epithelium has been reported in studies in mice. Exposure to high enough levels may have effects on the blood, resulting in chronic hemolytic anemia, and effects on the eyes, resulting in the development of cataracts. Cancer from naphthalene exposure has been observed in animals, but not humans. IARC has classified naphthalene as possibly carcinogenic to humans (Group 2B), and the ECHA C&L Inventory reports that naphthalene is suspected of causing cancer (Carc. 2).

Ethylbenzene

Ethylbenzene may be fatal if it is swallowed and enters the airways. Short term (acute) exposure to ethylbenzene can cause eye, skin, and throat irritation. It may have effects on the central nervous system including dizziness, and at very high exposure, lowering on consciousness. Long-term exposures orally and by inhalation have been shown to cause damage to the inner ear and hearing in animals. Long term or repeated exposure to high enough levels of ethylbenzene may have effects on the kidneys and liver, resulting in impaired functions, and repeated contact with skin may cause dryness and cracking. Animal studies indicate some evidence of adverse effects on the liver, kidney, thyroid, and pituitary gland. In a 2-year inhalation study in mice and rats, the animals were exposed to 0, 75, 250, and 750 ppm ethylbenzene 6 hours/day, 5 days/week. Renal effects were observed in male rats (renal tubule hyperplasia) and female rats (renal tubule adenoma and adenoma or carcinoma) exposed to 750 ppm. The incidence of adenoma in the testes of males was significantly greater than in the control group and exceeded the historical control range for inhalation studies. The incidences of alveolar/bronchiolar adenoma was increased in males and the incidence of hepatocellular adenoma was increased in females. IARC has classified ethylbenzene as possibly carcinogenic to humans (Group 2B). Studies do not provide conclusive evidence of reproductive effects. In one study, developmental effects were reported in animals but only at very high doses (≥ 1000 ppm) that are likely to be toxic to the mother. The relevance of these findings to humans is not clear at this time.

1,2,4-Trimethylbenzene

1,2,4-Trimethylbenzene may be fatal if it is swallowed and enters airways. Overexposure through inhalation and ingestion can cause confusion, dizziness, drowsiness, headache, and vomiting, cough, and sore throat. Short-term exposure to high enough levels through inhalation may cause respiratory irritation, and long-term overexposure may cause asthmatic bronchitis. Contact with skin can cause irritation, redness and dry skin. Contact with eyes can cause serious eye irritation, redness, and pain.

Health hazard and classification information

Skin Corrosion/Irritation Category No information available.

Serious eye damage/eye irritation No information available.

No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Kerosene (petroleum) 8008-20-6	A3***	Group 3***	-	-
Naphthalene 91-20-3	A3***	Group 2B***	Reasonably Anticipated***	X***
Ethylbenzene 100-41-4	A3***	Group 2B***	-	X***

Reproductive toxicity	No information available.
Target Organ Systemic Toxicant - Single Exposure	No information available.
Target Organ Systemic Toxicant - Repeated Exposure	Causes damage to organs through prolonged or repeated exposure.
Target organ effects	liver, kidney, Respiratory system, Eyes, Skin, Central nervous system, blood.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Additional Ecological Information Release of this product should be prevented from contaminating soil and water and from entering drainage and sewer systems. U.S.A. regulations require reporting spills of this material that could reach any surface waters. The toll free number to the U.S. Coast Guard National Response Center is (800) 424-8802

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphthalene 91-20-3	0.4: 72 h <i>Skeletonema costatum</i> mg/L EC50***	5.74 - 6.44: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 31.0265: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 0.91 - 2.82: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 1.6: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 1.99: 96 h <i>Pimephales promelas</i> mg/L LC50 static***	-	1.96: 48 h <i>Daphnia magna</i> mg/L EC50 Flow through 1.09 - 3.4: 48 h <i>Daphnia magna</i> mg/L EC50 Static 2.16: 48 h <i>Daphnia magna</i> mg/L LC50***
Ethylbenzene 100-41-4	438: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 4.6: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 1.7 - 7.6: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static 2.6 - 11.3: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static***	4.2: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 semi-static 7.55 - 11: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 9.6: 96 h <i>Poecilia reticulata</i> mg/L LC50 static 9.1 - 15.6: 96 h <i>Pimephales promelas</i> mg/L LC50 static 11.0 - 18.0: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 32: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static***	-	1.8 - 2.4: 48 h <i>Daphnia magna</i> mg/L EC50***
1,2,4-Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through***	-	6.14: 48 h <i>Daphnia magna</i> mg/L EC50***

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.

Component Information

Chemical Name	Partition coefficient
Naphthalene	3.6***

91-20-3	
Ethylbenzene 100-41-4	3.2***
1,2,4-Trimethylbenzene 95-63-6	3.63***

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number D001, U165

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Naphthalene 91-20-3	U165***	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145***	-	U165***
Ethylbenzene 100-41-4	-	Included in waste stream: F039***	-	-

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.***	-

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Naphthalene 91-20-3	Toxic***
Ethylbenzene 100-41-4	Toxic Ignitable***

14. TRANSPORT INFORMATION

DOT

UN/ID no UN1863
Proper Shipping Name FUEL, AVIATION, TURBINE ENGINE
Hazard Class 3
Packing group III
Reportable Quantity (RQ) (Naphthalene: RQ (kg)= 45.40)
Special Provisions 144, B1, IB3, T2, TP1
Description UN1863, FUEL, AVIATION, TURBINE ENGINE, 3, III
Emergency Response Guide Number 128

TDG

UN/ID no UN1863
Proper Shipping Name FUEL, AVIATION, TURBINE ENGINE
Hazard Class 3
Packing group III
Description UN1863, FUEL, AVIATION, TURBINE ENGINE, 3, III

MEX

UN/ID no UN1863
Proper Shipping Name FUEL, AVIATION, TURBINE ENGINE
Hazard Class 3
Special Provisions 223
Packing group III
Description UN1863, FUEL, AVIATION, TURBINE ENGINE, 3, III

IATA

UN/ID no UN1863
Proper Shipping Name FUEL, AVIATION, TURBINE ENGINE
Hazard Class 3
Packing group III
ERG Code 3L
Description UN1863, FUEL, AVIATION, TURBINE ENGINE, 3, III

IMDG

UN/ID no UN1863
Proper Shipping Name FUEL, AVIATION, TURBINE ENGINE
Hazard Class 3
Packing group III
EmS No. F-E, S-E
Special Provisions 223, 363
Description UN1863, FUEL, AVIATION, TURBINE ENGINE, 3, III, (38°C C.C.), Marine pollutant

15. REGULATORY INFORMATION

International Inventories

TSCA Listed
DSL/NDSL Listed
ENCS Not Listed
IECSC Listed
KECL Listed
PICCS Listed
AICS Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene 91-20-3	100 lb***	X***	X***	X***
Ethylbenzene 100-41-4	1000 lb***	X***	X***	X***

CERCLA

The CERCLA definition of hazardous substances contains a “petroleum exclusion” clause which exempts crude oil, fractions of crude oil, and products (both finished and intermediate) from the crude oil refining process and any indigenous components of such from the CERCLA Section 103 reporting requirements. However, other federal reporting requirements, including SARA Section 304, as well as the Clean Water Act may still apply.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Naphthalene - 91-20-3	Carcinogen***
Ethylbenzene - 100-41-4	Carcinogen***

U.S. State Right-to-Know Regulations

US State Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Kerosene (petroleum) 8008-20-6	X***	X***	X***
Naphthalene 91-20-3	X***	X***	X***
1,2,4-Trimethylbenzene 95-63-6	X***	X***	X***
Ethylbenzene 100-41-4	X***	X***	X***

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Revision Date 26-Jul-2017

Revision Note

No information available.

Disclaimer

Tesoro Companies, Inc. (Tesoro) provides the information on this Safety Data Sheet (SDS) in order to meet its obligations under 29 CFR 1910.1200, and does not hereby make any guarantee of product specifications or suitability for any particular purpose. Tesoro does not assume any liability arising out of the use of Tesoro's product or the use of information provided on this SDS. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all relevant information in the format of this document, since additional information may be necessary under exceptional conditions of use, and since Tesoro prepared this SDS based on information available on the date of its publication.

40, 41, 42, 43, 139, 141, 263, 1117, 1333, 1450, 45, 1132, 1227, 1278

End of Safety Data Sheet